



VINEYARDS



ORCHARDS

# BFM Auxiliary PTO Hydraulic Power Pack

Heavy duty rear 3-point attachment auxiliary hydraulic pump and oil tank unit allows you to operate attachments on a tractor independent of its own hydraulic system. Ideal for vine trimmer, leaf removers and similar front-mounted tractor implements. Available in two model sizes to fit a wide range of tractors and implement needs.









## STANDARD EQUIPMENT

- | 18 gallon or 26 gallon oil tank sizes
- | Pump flow rates of 10 gpm and 21 gpm with 540 rpm PTO
- | Oil return cooling radiator with fan (12V)
- | Oil pressure dial gauge at supply connector
- | Pressure relief valve set to 160 bar (2,350 psi)
- | In-line return oil filter with replaceable screen mesh cartridge
- | Oil level and temperature indicator site glass
- | Category I 3-point attachment
- | Includes Series 4 PTO driveline



## BFM AUXILIARY PTO HYRAULIC POWER PACK

						
MODEL	TANK CAPACITY	WEIGHT (FULL)	TRACTOR SIZE	DIMENSIONS	OIL FLOW RATE	WORKING PRESSURE
BFM-C305(18)	18 gallons	296 lbs	20–90 Hp	27" x 22" x 38" h	10 gpm	2,300 psi
BFM-C305(26)	26 gallons	390 lbs	20–90 Hp	27" x 22" x 42" h	21 gpm	2,300 psi

## IMPLEMENT FEATURES



Working Pressure Gauge



Oil Level/Temperature Site Glass



Return oil cooler with fan



Return oil mesh filter