



## ***BV2/3 Variable Deck Mower***

Heavy duty deck mower with a hydraulically adjustable cutting width. Two/three rotating blade groups with swing blades which can freely move to ensure a high speed of mowing efficiency with minimal horsepower requirements. Cut grass is discharged out the rear and rear sides of mower deck.








Fully adjustable wheels on the front and rear of deck determine the cutting height. Heavy duty all steel construction ensures many years of reliable and trouble-free service. Wide variety of model sizes fit row spacing between 5–14 feet.

### STANDARD EQUIPMENT

- | Cat. 1 & 2 three point linkage
- | 540 rpm PTO gearbox
- | Adjustable front and rear guide wheels
- | Swing blades on all cutting elements
- | Chain curtain protection at rear of mower
- | Heavy duty design and construction
- | Furnished with Cat.4/5 PTO driveline (depending on model size)

## BV2/3 VARIABLE WIDTH DECK MOWER

					
MODEL	NR. BLADES	TRACTOR SIZE	WEIGHT	WIDTH MIN (A)–MAX (B)	ROW SPACING
BV2—110-145	4	40–100 Hp	946	44–57"	5–7'
BV2—125-175	4	40–100 Hp	1,035	51–68"	6–8'
BV2—140-195	4	40–100 Hp	1,122	56–78"	
BV2—160-230	4	50–100 Hp	1,276	65–90"	7–9'
BV2—190-260	4	50–100 Hp	1,518	76–103"	8–10'
BV2—220-300	4	50–100 Hp	1,738	88–119"	9–11'
BV2—250-340	4	60–100 Hp	2,178	98–134"	10–13'
BV3—180-260	6	60–100 Hp	1,386	72–103"	8–11'
BV3—195-290	6	60–100 Hp	1,430	78–115"	9–12'
BV3—250-360	6	60–100 Hp	1,980	100–144"	10–14'



Hydraulically adjustable working width